



Tiap unit **SANKELUX** memiliki kapasitas SKVA dan ekspansi sampai 200VA
 — Ditengkapi dengan **MULTI INFORMATION DISPLAY (MID)** untuk memudahkan penggunaan.



| Model | SLM 1K-24 | SLM 2K-24 | SLM 3K-24 |
|---------------------------------------|--|--|--|
| Rated Power | 1000VA/800W | 2000VA/1600W | 3000VA/2400W |
| INPUT | | | |
| Voltage | 120VAC or 230 VAC | 230 VAC | 230 VAC |
| Selectable Voltage Range | 95-140VAC or 170-230VAC (For Personal Computers) 65-140VAC or 90-280VAC (For Home Appliances) | 170-280VAC (For Personal Computers) 90-280VAC (For Home Appliances) | 170-280VAC (For Personal Computers) 90-280VAC (For Home Appliances) |
| Frequency Range | 50Hz/60Hz (auto sensing) | 50Hz/60Hz (auto sensing) | 50Hz/60Hz (auto sensing) |
| OUTPUT | | | |
| AC Voltage Regulation | 110/120VAC±5% or 230VAC ±5% | 230VAC ±5% | 230VAC ±5% |
| Surge Power | 2000VA | 4000VA | 4000VA |
| Efficiency (peak) | 90%-93% | 93% | 93% |
| Transfer Time | 10 ms(for personal computers) 20 ms (for home appliances) | 10 ms(for personal computers) 20 ms (for home appliances) | 10 ms(for personal computers) 20 ms (for home appliances) |
| Waveform | Pure Sine Wave | Pure Sine Wave | Pure Sine Wave |
| BATTERY & AC CHARGER | | | |
| Battery Voltage | 24 VDC | 24 VDC | 24 VDC |
| Floating Charge Voltage | 27 VDC | 27 VDC | 27 VDC |
| Overcharge Protection | 31 VDC | 31 VDC | 31 VDC |
| Maximum Charge Current | 10 A or 10 A/20A | 20 A or 30 A | 20 A or 30 A |
| SOLAR CHARGER | | | |
| Maximum PV Array Power | 600 W | 600 W | 600 W |
| MPPT Range @ Operating Voltage | 30VDC-66VDC | 30VDC-66VDC | 30VDC-66VDC |
| Maximum PV Array Open Circuit Voltage | 75VDC | 75VDC | 75VDC |
| Maximum Charging Power | 25A | 25A | 25A |
| Maximum Efficiency | 98% | 98% | 98% |
| Standby Power Consumption | 2W | 2W | 2W |
| PHYSICAL | | | |
| Dimension D x W x H (mm) | 128 x 272 x 355 | 128 x 272 x 355 | 128 x 272 x 355 |
| Net Weight (Kg) | 7.4 | 7.6 | 8.0 |
| OPERATING ENVIRONMENT | | | |
| Humidity | 5% to 95% | 5% to 95% | 5% to 95% |
| Operating Temperature | 0°C-55°C | 0°C-55°C | 0°C-55°C |
| Storage Temperature | -15°C-60°C | -15°C-60°C | -15°C-60°C |
| Inverter Power | 800W | 1600W | 2400W |
| Pmax Generated from Solar Charger | 25Amp,600W | 25Amp,600W | 25Amp,600W |
| Best Panel Configuration | 500Wp (125 Wp x 4 Pcs) | 500Wp (125 Wp x 4 Pcs) | 500Wp (125 Wp x 4 Pcs) |

Head Office *PT.SANKEINDO* :
Jalan Pahlawan Seribu Komplek Golden Boulevard
Blok.H2 No.43-46 Serpong Tangerang 15322
Phone : (021) 53161139
Fax : (021) 53161135
Email : sales@sankeindo.co.id

Branch Office :
Jln.Kinibalu No.56
Kel.Antasan Besar Kec.Banjarmasin Tengah
Kota Banjarmasin – Kalimantan Selatan 70114
Phone : (0511) 3353615
Fax : (0511) 3353615